

ALUMINIUM PIN

- Easy to cut, bend and mount
- Corrosion free


ALUMINIUM PIN WITH SAFE TIP

- Provides safe working environment
- Needs no pin cap



	BASE	PIN	FASTENING CLIPS
Construction	Reinforced Galvanized Steel	Aluminium	Galvanized Steel
Dimensions	50 x 50 mm (2" x 2") 30x30 mm (1.2" x 1.2")	Ø 3 mm ± 0.3 mm Ø 2.2 mm ± 0.2 mm	Outside Ø30 mm (1.2")
Thickness	0.35 mm	-	0.30 mm
Adhesive	Acrylic Adhesive		
Pin Length	30 mm to 180 mm (1.2" to 7.0")		
Temperature Range	-10°C to +80°C (+14°F to +176°F) Application Temperature has to be > +10°C (+50°F) Ideal temperature for application ~ 23 °C		

AFSPIN PACKING DETAILS		
Base Dimension: 50x50 mm		
Pin Length	Packing type	Package Amount
40 mm	Carton Box	500 Pieces with washer/ Box
50 mm	Carton Box	500 Pieces with washer/ Box
60 mm	Carton Box	500 Pieces with washer/ Box

 80 mm and 100 mm are available a request.



“ AFS cares about the workmen’s safety! ”



Operational temperature range of AFSPIN is -10 °C / +80 °C. Application temperature has to be above +10 °C. The surface applied on has to be free of any residues, dust, grease, oil, etc.